


CERTIFICATE OF QUALITY

Page: 1/1
Date of issue: June 16, 2008

1.	PRODUCT NAME LEVELLING RENDER (Renovirni omet) Reinforced and Filling Render for Façade Repairs
2.	GENERAL DESCRIPTION Dry mix microfibre reinforced polymer-cement based mortar.
3.	COMPOSITION Cement, hydrated lime, organic additives and mineral aggregates up 1mm. The render contains special water-repellent additives and micro-reinforced fibers.
4.	PHYSICAL AND CHEMICAL PROPERTIES 4.1. APPEARANCE: powder 4.2. COLOUR: grey 4.3. BULK DENSITY (kg/m ³ /20°C): app.1120 4.4. pH (20°C): 11,5 – 13,0 (paste form) 4.5. FLASH POINT: / 4.6. DRY FILM THICKNESS (mm): up to 4 mm (one layer) 4.7. WVTR μ (-): $\mu < 30$ 4.8. VALUE $S_d(m)$, $d = 6$ mm: $S_d < 0,2$ (EN ISO 7783-2, Class 2, medium) 4.9. LIQUID WATER PERMEABILITY (kg/m ² h ^{0,5}): $W_{24h} < 0,11$ (EN 1062 –3, Class 2, medium) 4.10. ADHESION TO MINERAL RENDER (EN 1015-12): $> 0,7$ N/mm ²
5.	HAZARDS IDENTIFICATION This product is classified as HAZARDOUS according to EC-directive EU 1999/45/EC. Xi, IRRITANT , contains cement and lime.
6.	TEST REPORTS ZAG Ljubljana, Report P 13/04 – 410-2, 12. 02. 2004  EN 998-1
7.	The document was issued with the intention to prove the quality of the product according to specific requirements. This construction product is a mineral based render due to EN 998-1 and must bear CE-marking. EC Declaration of Conformity is issued. R&D Coordination Manager Damjan Saksida, B. Sc. Chem. Techn.