



CERTIFICATE OF QUALITY

Page: 1/1
Date of issue: 02/15/2013

1.	PRODUCT NAME JUBOGLET POWDERY LEVELLING COMPOUND FOR INTERIOR
2.	AREA OF APPLICATION Plaster for levelling of larger wall and ceiling surfaces, of irregularities of up to 8mm layer thickness. May be used also as joint filler (grout) between gypsum-cardboards, as filler of 8mm deep vaultings, cuts, holes and other similar on interior walls and ceilings.
3.	COMPOSITION Plaster on the base of gypsum, polymer binders, cellulose thickener, calcite fillers.
4.	PHYSICAL AND CHEMICAL PROPERTIES
4.1.	APPEARANCE: powdery
4.2.	COLOUR: grey
4.3.	BULK DENSITY (kg/m ³ /20°C): about 930
4.4.	POT LIFE/OPEN TIME: > 50 minutes (EN 13279-1)
4.5.	VAPOUR PERMEABILITY μ (-): < 10 (EN ISO 1015-19)
4.6.	WVTR: Sd < 0.08m with d=8.0 mm (EN ISO 1015-19)
4.7.	BOND STRENGTH (gypsum cardboard): > 0.30 N/mm ² decomposition within gypsum-cardboard (EN 13279-2)
	BOND STRENGTH (concrete+Akril Emulsion primer): > 0.09 N/mm ² (EN 13279-2)
4.8.	COMPRESSIVE STRENGTH: ≥ 2 N/mm ² (EN 13279-2)
	BENDING STRENGTH: ≥ 1 N/mm ² (EN 13279-2)
5.	HAZARDOUS IDENTIFICATION Under the criteria which are defined by the regulation Classification, packaging and labelling of dangerous substances harmonised with the directives DSD EU 67/458/EC and DPD 1999/45/EC, and according to REACH 1907/2006/EC and CLP 1272/2008/EC, the chemical composite as a product is Not Classified as a dangerous preparation.
6.	TEST REPORTS /
7.	We assure that the characteristics of this product meet the specified requirements. This document was issued with the intention to prove the quality of the product according to specific requirements. In case of essential changes of the properties under point 4, a new certificate shall be issued. A CE-Declaration of conformity is issued.

Responsible :
Head of research field
Dr. Petra Brulc, dipl. chem. ing.




 TRC JUB d.o.o.
 Dol pri Ljubljani 28
 SI-1262 Dol pri Ljubljani
 Slovenija

